



Specifications

| |  |  |
|----------------------------------|--|--|
| Pump Model | SamplePro 3/4" | SamplePro 1-3/4" |
| Outside Diameter | 0.75 in (19 mm) | 1.75 in (47 mm) |
| Length | 10.75 in (273 mm) with Push-In Fittings 9.18 in (233 mm) from Bottom of pump to centerline of inlet | 14.75 in (375 mm) with Push-In Fittings 16.5 in (419 mm) with Compression Fittings 12.1 in (307 mm) from Bottom of pump to centerline of inlet |
| Weight | 0.5 lbs (0.23 Kg) | 4.25 lbs (1.93 Kg) |
| Maximum Lift | 200 ft (61m) | 200 ft (61m) |
| Volume per Stroke* | 0.33 - 0.50 oz (10 - 15 ml) | 3.34 oz (100 ml) |
| Materials of Construction | | |
| • Body and Cover | 316 Stainless Steel | 316 Stainless Steel |
| • Inlet, Discharge & Head | 303 Stainless Steel | 303 Stainless Steel |
| • Bladder | Polyethylene | Polyethylene |
| • O-Rings | Viton® | Viton® |
| Fitting Type | Push-in Fitting w/ 316 Stainless Steel Grab Plate | Push-in Fitting w/ 316 Stainless Steel Grab Plate |
| • Air Fitting | 1/8 in (3.2mm) OD | 1/4" (6.4 mm) O.D. |
| • Fluid Discharge | 1/4" (6.4 mm) O.D. | 1/4" (6.4 mm) or 3/8 in (9.5mm) O.D. |
| Pump Part Numbers | SP-3/4-P | MP-SP-4P (1/4" discharge, push-in fittings) MP-SP-4C (1/4" discharge, compression fittings) MP-SP-6P (3/8" discharge, push-in fittings) MP-SP-6C (3/8" discharge, compression fittings) |

* Pumped volume per stroke increases with greater depths.
Viton® is a registered trademark of DuPont Dow Elastomers.