



Specifications

		
Pump Model	SamplePro 3/4"	SamplePro 1-3/4"
Outside Diameter	0.75 in (19 mm)	1.75 in (47 mm)
Length	10.75 in (273 mm) with Push-In Fittings 9.18 in (233 mm) from Bottom of pump to centerline of inlet	14.75 in (375 mm) with Push-In Fittings 16.5 in (419 mm) with Compression Fittings 12.1 in (307 mm) from Bottom of pump to centerline of inlet
Weight	0.5 lbs (0.23 Kg)	4.25 lbs (1.93 Kg)
Maximum Lift	200 ft (61m)	200 ft (61m)
Volume per Stroke*	0.33 - 0.50 oz (10 - 15 ml)	3.34 oz (100 ml)
Materials of Construction		
• Body and Cover	316 Stainless Steel	316 Stainless Steel
• Inlet, Discharge & Head	303 Stainless Steel	303 Stainless Steel
• Bladder	Polyethylene	Polyethylene
• O-Rings	Viton®	Viton®
Fitting Type	Push-in Fitting w/ 316 Stainless Steel Grab Plate	Push-in Fitting w/ 316 Stainless Steel Grab Plate
• Air Fitting	1/8 in (3.2mm) OD	1/4" (6.4 mm) O.D.
• Fluid Discharge	1/4" (6.4 mm) O.D.	1/4" (6.4 mm) or 3/8 in (9.5mm) O.D.
Pump Part Numbers	SP-3/4-P	MP-SP-4P (1/4" discharge, push-in fittings) MP-SP-4C (1/4" discharge, compression fittings) MP-SP-6P (3/8" discharge, push-in fittings) MP-SP-6C (3/8" discharge, compression fittings)

* Pumped volume per stroke increases with greater depths.
Viton® is a registered trademark of DuPont Dow Elastomers.